

SHENZHEN XIEJIA ELECTRONICS CO.,LTD. 深圳市协佳电子有限公司		文件编号 发布日期	XJ-SP-3145 2004年4月6日
SPECIFICATION 规格书		第 A 版	第 1 页 共 3 页
MODEL NO. 产品名称. TC-0090			
DRAWN 制订		APPD. 审批	
1. RATING (额定值) : DC 5V 0.1mA~5mA			
2. ELECTRICAL CHARACTERISTICS (电气性能规格):			
ITEM 项目		TEST CONDITIONS 测试条件	PERFORMANCE 规格
2.1	CONTACT RESISTANCE 接触电阻	MEASURED AT 1KHz SMALL CURRENT(10 mA OR LESS) 在 1KHz 微小电流(10mA 以下)测试.	1Ω MAX. 1 欧以下。
2.2	INSULATION RESISTANCE 绝缘电阻	APPLY A VOLTAGE OF 100V DC FOR 1 MIN. TO FOLLOWING PORTIONS AFTER WHICH MEASUREMENT SHALL BE MADE. (1) BETWEEN BODY AND CONDUCTOR. (2) BETWEEN CONDUCTORS NOT TO BE CONTACT. 输入 100V DC 电压 1 分钟,按以下接触方法测试: (1) 接触端子之间. (2) 胶座体与排脚之间.	100MΩ MIN. 100 兆欧以上。
2.3	DIELECTRIC STRENGTH 耐电压	AC 100V (50-60Hz)FOR 1 MIN TRIP CURRENT:2 mA (1) BETWEEN TERMINALS. (2) BETWEEN INDIVIDUAL TERMINALS AND FRAME. 输入 AC 100V(50-60Hz)电压,1 分钟感度电流为 2 mA,按 以下接触方法测试: (1) 排脚相互之间 (2) 排脚与外壳之间	WITHOUT DAMAGE TO PARTS ARCING OR BREAKDOWN ETC. 没有绝缘破坏等异常。
3. MECHANICAL CHARACTERISTICS (机械性能规格)			
ITEM 项目		TEST CONDITIONS 测试条件	PERFORMANCE 规格
3.1	OPERATING FORCE 作动力		35gf MAX.
3.2	TERMINAL STRENGTH 端子强度	A STATIC LOAD OF (50 gf) SHALL BE APPLIED TO THE TIP OF THE TERMINAL FOR 15 SEC IN ANY DIRECTION. 在任意一个方向的先端加上(50 gf)力度测试,时间为 15 秒.	MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED WITHOUT DAMAGE OR EXCESSIVE LOOSENESS OF ACTUATOR. 在端子中没有裂开、松动等异 常,满足于机械、电器性能。
3.3	STANDARD ATMOSPHERIC CONDITIONS 测试标准状态	UNLESS OTHERWISE SPECIFIED. THE STANDARD RANGE OF ATMOSPHERIC CONDITIONS FOR MAKING MEASUREMENTS AND TESTS ARE AS FOLLOWS: (1) AMBIENT TEMPERATURE: 5℃ TO 35℃ (2) RELATIVE HUMIDITY : 45% TO 85% (3) AIR PRESSURE : 86Kpa TO 106Kpa 在没有指定的情况下测试温度、湿度、气压如下: (1) 温度为 5℃~35℃. (2) 湿度为 45%~85%. (3) 气压为 80Kpa~106Kpa.	

SHENZHEN XIEJIA ELECTRONICS CO., LTD. 深圳市协佳电子有限公司		文件编号 发布日期	XJ-SP-3145 2004年4月6日	
SPECIFICATION 规格书		第 A 版	第 2 页 共 3 页	
3.4	PRACTICAL TEMPERATURE RANGE 使用温度范围	-16°C~+60°C. 在-16°C~+60°C温度内使用.		
4. DURABILITY (耐久性):				
ITEM 项目		TEST CONDITIONS 测试条件	PERFORMANCE 规格	
4.1	SOLDERABILITY TEST 可焊性试验	THE TOP OF THE TERMINALS SHALL BE DIPPED 2mm IN THE SOLDER BATH OF 230±5°C FOR 3±0.5 SECONDS. 端子顶部被浸入锡焊池中 2mm 深, 温度为 230±5°C, 时间为 3±0.5 秒.	THE AREA OF SOLDERING. SHOULD BE OVER 90% 焊接面积要有 90%以上.	
4.2	RESISTANCE TO SOLDERING HEAT TEST 耐焊性试验	(1). TEMPERATURE AND IMMERSING TIME 温度及浸锡时间		
			TEMPERATURE 温度 (°C)	TIME 时间 (s)
		DIP SOLDERING 浸 锡	260±5	3±1
		MANUAL SOLDERING 手 焊	360±10	3±1
		(2). IMMERSION DEPTH: IMMERSION DEPTH UP TO THE SURFACE OF THE BOARD THICKNESS OF PRINTED WIRING BOARD 1.6mm 浸锡深度: 温室锡深度至基板 (PCB) 表面, 基板厚度为 1.6mm.	THERE SHALL BE NO DEFORMATION OF THE SWITCH. MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED. 本体无变形, 满足于机械、电气性能.	
		(3). WAVE SOLDERING 波峰焊 (A) 260±5°C 5 SCE. MAX. (B) PREHEAT TIME SHALL BE 30 SECONDS MAX. AT 100°C MAX. 预热温度 100°C 以下, 30 秒以内完成.		
4.3	LIFE TEST 寿命试验	WITHOUT LOAD: AN ACTUATOR SHALL BE SUBJECT TO 100,000 CYCLES AT A SPEED OF 15~20 CYCLES FOR 1 MIN. 无负荷: 操作者以每分钟 15~20 次的频率作 100,000 回之无负荷测试.	(1) CONTACT RESISTANCE SHALL BE 2Ω MAX. (2) MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED. (1) 接触电阻不能超于 2Ω. (2) 其它、满足机械、电器性能.	
4.4	HEAT TEST 耐热试验	THE SWITCH SHALL BE STORED AT A TEMPERATURE OF 85±2°C FOR 96 HOURS AND THEN IT SHALL BE SUBJECT TO THE CONTROLLED RECOVERY CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE. 放置在温度 85±2°C 中测试 96 小时后, 再放置正常室温中 1 小时来测定	THERE SHALL BE NO DAMAGE ON APPEARANCE. MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED. 外观无异常, 满足于机械、电器性能.	

SHENZHEN XIEJIA ELECTRONICS CO., LTD. 深圳市协佳电子有限公司		文件编号	XJ-SP-3145
SPECIFICATION 规格书		发布日期	2004年4月6日
		第A版	第3页共3页

4.5	COLD TEST 耐冷试验	<p>THE SWITCH SHALL BE STORED AT A TEMPERATURE OF <math>-20\pm 2^{\circ}\text{C}</math> FOR 96 HOURS. AND THEN IT SHALL BE SUBJECTED TO THE CONTROLLED RECOVER CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.</p> <p>放置在温度<math>-20\pm 2^{\circ}\text{C}</math>中96小时后,再放置常温常湿中1小时来测定。</p>	<p>THERE SHALL BE NO DEFORMATION OR CRACKS IN MOLDED PART.</p> <p>外观无异常,满足于机械、电器性能。</p>
4.6	HUMIDITY TEST 潮湿试验	<p>THE SWITCH SHALL BE STORED AT A TEMPERATURE OF <math>40\pm 2^{\circ}\text{C}</math> AND A HUMIFITY OF 90% TO 95% FOR 96 HOURS.THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITION FOR 1 Hr FOR OTHER PROCEDURES BE MADE.</p> <p>放置 <math>40\pm 2^{\circ}\text{C}</math>.的相对湿度为90~95%环境中96小时后,再将样版放在正常环境1小时后进行测试。</p>	

XIEJIA  
ELECTRONICS