

SHENZHEN XIEJIA ELECTRONICS CO.,LTD. 深圳市协佳电子有限公司		文件编号	XJ-SP-3239a
		发布日期	2006年3月7日
SPECIFICATION 规格书		第A版	第1页共3页
MODEL NO. 产品名称. TD-85XU TD-85XA TD-85EA TD-85EU			
DRAWN 制订		APPD. 审批	
1. RATING (额定值) : DC 12V 50mA			
2. ELECTRICAL CHARACTERISTICS (电气性能规格):			
ITEM 项目		TEST CONDITIONS 测试条件	PERFORMANCE 规格
2.1	CONTACT RESISTANCE 接触电阻	MEASURED AT 1KHz SMALL CURRENT(100 mA OR LESS) 在1KHz 微小电流(100mA 以下)测试.	100mΩ MAX. 100 毫欧以下.
2.2	INSULATION RESISTANCE 绝缘电阻	APPLY A VOLTAGE OF 100V DC FOR 1 MIN. TO FOLLOWING PORTIONS AFTER WHICH MEASUREMENT SHALL BE MADE. (1) BETWEEN BODY AND CONDUCTOR. (2) BETWEEN CONDUCTORS NOT TO BE CONTACT. 输入100V DC 电压1分钟,按以下接触方法测试: (1) 接触端子之间. (2) 胶座体与排脚之间.	100MΩ MIN. 100 兆欧以上.
2.3	DIELECTRIC STRENGTH 耐电压	AC 250V (50-60Hz)FOR 1 MIN TRIP CURRENT:0.5 mA (1) BETWEEN TERMINALS. (2) BETWEEN INDIVIDUAL TERMINALS AND FRAME. 输入 AC 250V(50-60Hz)电压,1分钟感度电流为0.5 mA,按 以下接触方法测试: (1) 排脚相互之间 (2) 排脚与外壳之间	WITHOUT DAMAGE TO PARTS ARCING OR BREAKDOWN ETC. 没有绝缘破坏等异常.
3. MECHANICAL CHARACTERISTICS (机械性能规格)			
ITEM 项目		TEST CONDITIONS 测试条件	PERFORMANCE 规格
3.1	OPERATING FORCE 作动力		见第三页
3.2	TERMINAL STRENGTH 端子强度	A STATIC LOAD OF (300 gf) SHALL BE APPLIED TO THE TIP OF THE TERMINAL FOR 1 MIN IN ANY DIRECTION. 在任意一个方向的先端加上(300 gf)力度测试,时间为1分钟.	MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED WITHOUT DAMAGE OR EXCESSIVE LOOSENESS OF ACTUATOR. 在端子中没有裂开.松动等异 常, 满足于机械、电器性能.
3.3	STANDARD ATMOSPHERIC CONDITIONS 测试标准状态	UNLESS OTHERWISE SPECIFIED. THE STANDARD RANGE OF ATMOSPHERIC CONDITIONS FOR MAKING MEASUREMENTS AND TESTS ARE AS FOLLOWS: (1) AMBIENT TEMPERATURE: 5℃ TO 35℃ (2) RELATIVE HUMIDITY : 45% TO 85% (3) AIR PRESSURE : 80Kpa TO 106Kpa 在没有指定的情况下测试温度、湿度、气压如下: (1) 温度为5℃~35℃. (2) 湿度为45%~85%. (3) 气压为80Kpa~106Kpa.	


SHENZHEN XIEJIA ELECTRONICS CO.,LTD. 深圳市协佳电子有限公司		文件编号	XJ-SP-3239a
SPECIFICATION 规格书		发布日期	2006年3月7日
		第A版	第2页共3页
3.4	PRACTICAL TEMPERATURE RANGE 使用温度范围	-16℃~+60℃. 在-16℃~+60℃温度内使用。	
4. DURABILITY (耐久性):			
ITEM 项目		TEST CONDITIONS 测试条件	PERFORMANCE 规格
4.1	LIFE TEST 寿命试验	WITHOUT LOAD: AN ACTUATOR SHALL BE SUBJECT TO 100,000 CYCLES AT A SPEED OF 60 CYCLES FOR 1 MIN. 无负荷: 操作者以每分钟60次的频率作100,000回之无负荷测试。	(1) CONTACT RESISTANCE SHALL BE 200mΩ MAX. (2) MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED. (1) 接触电阻不能超于200mΩ. (2) 其它、满足于机械、电器性能。
4.2	HEAT TEST 耐热试验	THE SWITCH SHALL BE STORED AT A TEMPERATURE OF 85±2℃ FOR 96 HOURS. AND THEN IT SHALL BE SUBJECTED TO THE CONTROLLED RECOVERY CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE. 放置在温度85±2℃中测试96小时后,再放置正常室温中1小时来测定	THERE SHALL BE NO DAMAGE ON APPEARANCE. MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED. 外观无异常,满足于机械,电器性能。
4.3	COLD TEST 耐冷试验	THE SWITCH SHALL BE STORED AT A TEMPERATURE OF -25±3℃ FOR 96 HOURS. AND THEN IT SHALL BE SUBJECTED TO THE CONTROLLED RECOVER CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE. 放置在温度-25±3℃中96小时后,再放置常温常湿中1小时来测定。	
4.4	HUMIDITY TEST 潮湿试验	THE SWITCH SHALL BE STORED AT A TEMPERATURE OF 40±2℃AND A HUMIFITY OF 90% TO 96% FOR 96 HOURS.THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITION FOR 1 Hr FOR OTHER PROCEDURES BE MADE. 放置40±2℃.的相对湿度为90~96%环境中96小时后,再将样版放在正常环境1小时后进行测试。	THERE SHALL BE NO DEFORMATION OR CRACKS IN MOLDED PART. 外观无异常,满足于机械、电器性能。

4.5

SOLDERING  
CONDITIONS  
焊锡条件

(1)HAND SOLDERING:  
DEVICE:SOLDER IRON  
手焊:  
工具:烙铁  
A.350℃ Max.3sec.Max.  
B.270℃ Max.5sec.Max.

(2)REFLOW SOLDERING  
回流焊  
240℃ Max. 3sec.MaX.



THERE SHALL BE NO DEFORMATION  
OR CRACKS IN MOLDED PART.  
外观无异常,满足于机械、电器性能。

CODE	OFORCE
X	160gf±50gf
Y	250gf±100gf