

SHENZHEN XIEJIA ELECTRONICS CO., LTD. 深圳市协佳电子有限公司		文件编号	XJ-SP-4020
SPECIFICATION 规格书		发布日期	2007年12月23日
		第B版	第1页共3页
MODEL NO. 产品名称 . PB-22E78 PB-22E88			
DRAWN 制订		APPD. 审批	
1. RATING (额定值)		: DC 30V 0.1A	
2. FUNCTION (接触型式)		: 2P2T	
3. TIMING		: NON-SHORTING	
3. ELECTRICAL CHARACTERISTICS (电气性能规格):			
ITEM 项目	TEST CONDITIONS 测试条件		PERFORMANCE 规格
3.1	CONTACT RESISTANCE 接触电阻	MEASURED AT 1KHz SMALL CURRENT(100 mA OR LESS) 在1KHz微小电流(100mA以下)测试.	30mΩ MAX. 30毫欧以下。
3.2	INSULATION RESISTANCE 绝缘电阻	APPLY A VOLTAGE OF 500V DC FOR 1 MIN. TO FOLLOWING PORTIONS AFTER WHICH MEASUREMENT SHALL BE MADE. (1) BETWEEN BODY AND TERMINAL. (2) BETWEEN TERMINALS. 输入500V DC电压1分钟,按以下接触方法测试: (1) 外壳与排脚之间. (2) 端子之间.	100MΩ MIN. 100兆欧以上。
3.3	DIELECTRIC STRENGTH 耐电压	AC 500V (50-60Hz)FOR 1 MIN TRIP CURRENT:0.5 mA (1) BETWEEN TERMINALS. (2) BETWEEN INDIVIDUAL TERMINAL AND FRAME. 输入AC 500V(50-60Hz)电压,1分钟感度电流为0.5 mA,按 以下接触方法测试: (1) 排脚相互之间 (2) 排脚与外壳之间	WITHOUT DAMAGE SUCH AS INSULATION BREAKDOWN. 没有绝缘破坏等异常。
4 .MECHANICAL CHARACTERISTICS (机械性能规格)			
ITEM 项目	TEST CONDITIONS 测试条件		PERFORMANCE 规格
4.1	OPERATING FORCE 作动力		350gf±150gf
4.2	TERMINAL STRENGTH 端子强度	A STATIC LOAD OF (300 gf) SHALL BE APPLIED TO THE TIP OF THE TERMINAL FOR 1 MIN. IN ANY DIRECTION. 在任意一个方向的先端上加力度(300 gf)1分钟。	MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED WITHOUT DAMAGE OR EXCESSIVE LOOSENESS OF ACTUATOR. 在端子中没有裂开、松动等异 常, 满足于机械、电器性能。
4.3	STANDARD ATMOSPHERIC CONDITIONS 测试标准状态	UNLESS OTHERWISE SPECIFIED. THE STANDARD RANGE OF ATMOSPHERIC CONDITIONS FOR MAKING MEASUREMENTS AND TESTS ARE AS FOLLOWS: (1) AMBIENT TEMPERATURE: 5℃ TO 35℃ (2) RELATIVE HUMIDITY : 45% TO 85% (3) AIR PRESSURE : 86Kpa TO 106Kpa 在没有指定的情况下测试温度、湿度、气压如下: (1) 温度为5~35℃ (2) 湿度为45%~85% (3) 气压为86Kpa~106Kpa	

SHENZHEN XIEJIA ELECTRONICS CO.,LTD. 深圳市协佳电子有限公司		文件编号 发布日期	XJ-SP-4020 2007年12月23日		
SPECIFICATION 规格书		第 A 版	第 2 页 共 3 页		
4.4	PRACTICAL TEMPERATURE RANGE 使用温度范围	-16℃~+60℃ 在-16℃~+60℃温度内使用			
5. ENDURANCE CHARACTERISTICS (耐久性):					
ITEM 项目		TEST CONDITIONS 测试条件		PERFORMANCE 规格	
5.1	SOLDERABILITY TEST 可焊性试验	THE TOP OF THE TERMINALS SHALL BE DIPPED 2mm IN THE SOLDER BATH OF 230±5℃ FOR 3±0.5 SECONDS. 端子顶部被浸入锡焊池中 2mm 深, 温度为 230±5℃, 时间为 3±0.5 秒.		THE AREA OF SOLDERING SHOULD BE OVER 75% 焊接面积要有 75%以上.	
5.2	RESISTANCE TO SOLDERING HEAT TEST 耐焊性试验	(1). TEMPERATURE AND IMMERSING TIME 温度及浸锡时间			THERE SHALL BE NO DEFORMATION OF THE SWITCH. MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED. 本体无变形, 满足于机械、电气性能.
			TEMPERATURE 温度 (°C)	TIME 时间 (s)	
		DIP SOLDERING 浸 锡	260±5	3±1	
		MANUAL SOLDERING 手 焊	360±10	3±1	
		(2). IMMERSION DEPTH: IMMERSION DEPTH UP TO THE SURFACE OF THE BOARD THICKNESS OF PRINTED WIRING BOARD 1.6mm 浸锡深度: 浸锡深度至基板 (PCB) 表面, 基板厚度为 1.6mm.			
5.3	LIFE TEST 寿命试验	WITHOUT LOAD: AN ACTUATOR SHALL BE SUBJECT TO 100,000 CYCLES AT A SPEED OF 20 CYCLES FOR 1 MIN. 无负荷: 操作者以每分钟 20 次的频率作 100,000 回之无负荷测试.		(1) CONTACT RESISTANCE (接触电阻) 100mΩ MAX. 100 毫欧以下. (2) INSULATION RESISTANCE (绝缘电阻) 50MΩ MIN. 50 兆欧以上. (3) WITHSTAND VOLTAGE (耐电压) AC 500V, 1 MINUTE. AC 500V 1 分钟. (4) OPERATING FORCE (作动力) ±30% INITIAL VALUE. 变化范围初始值±30%. (5) WITHOUT DAMAGE TO PARTS ARCING OR BREAKDOWN ETC. (测试后外表无损伤, 并且满足机械性能)	

SHENZHEN XIEJIA ELECTRONICS CO.,LTD. 深圳市协佳电子有限公司		文件编号	XJ-SP-4020
SPECIFICATION 规格书		发布日期	2007年12月23日
		第A版	第3页 共3页
5.4	COLD TEST 耐冷试验	<p>THE SWITCH SHALL BE STORED AT A TEMPERATURE OF $-25\pm 3^{\circ}\text{C}$ FOR 96 HOURS AND THEN IT SHALL BE SUBJECTED TO THE CONTROLLED RECOVERY CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.</p> <p>放置在温度$-25\pm 3^{\circ}\text{C}$中96小时后,再放置常温常湿中1小时来测定。</p>	<p>THERE SHALL BE NO DAMAGE ON APPEARANCE. MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED. 外观无异常, 满足于机械, 电器性能。</p>
5.5	HEAT TEST 耐热试验	<p>THE SWITCH SHALL BE STORED AT A TEMPERATURE OF $85\pm 2^{\circ}\text{C}$ FOR 96 HOURS.AND THEN IT SHALL BE SUBJECTED TO THE CONTROLLED RECOVERY CONDITIONS FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.</p> <p>放置在温度$85\pm 2^{\circ}\text{C}$中测试96小时后,再放置正常室温中1小时来测定。</p>	
5.6	HUMIDITY TEST 潮湿试验	<p>THE SWITCH SHALL BE STORED AT A TEMPERATURE OF $40\pm 2^{\circ}\text{C}$ AND A HUMIDITY OF 90% TO 95% FOR 96 HOURS.THEN THE SWITCH SHALL BE MAINTAINED AT STANDARD ATMOSPHERIC CONDITION FOR 1 HOUR AFTER WHICH MEASUREMENT SHALL BE MADE.</p> <p>放置$40\pm 2^{\circ}\text{C}$的相对湿度为90%~95%环境中96小时后,再将样版放在正常环境1小时后进行测试。</p>	